Belinea

[Belinea 10 30 85]

The Belinea 10 30 85 is the ideal monitor for all requirements in the office area. This 17 inch model offers needle sharp image representation as well as detailed resolutions and thus the necessary prerequisite for ergonomically perfect operating. Furthermore, owing to the numerous OSD options, this model can be adjusted to the user's individual needs. The high level regarding ergonomics, emission, ecology and energy is proved by certifications like TCO 99 and TUEV Ergo. The Belinea 10 30 85 is standing in the tradition of the extremely successful Belinea 10 30 40 which set standards especially in public authorities.

CRT	
screen size	17"
viewable screen size in inch / cm	15,94 / 40,49
max. picture size (w x h) in mm	324 x 243
max. resolution	1600 x 1200
ergonomic resolution	1024 x 768
mask pitch (diagonal) in mm	0,26
mask pitch (horizontal) in mm	0,22
dynamic focus	•
shadow mask / aperture grille	• / –
coating	ARAS
screen treatment	Spin method

electrical data	
horizontal frequency in kHz	30-86
vertical frequency in Hz	50-160
bandwidth in MHz	150
input voltage 110-230V, 50-60 Hz	•
power consumption in Watt	
(On / Stand-by / Suspend / Off-Mode)	75 / 3 / 3 / 3

features	
factory / user defined modes	10 / 8
OSD	•

OSD controls	
brightness / contrast*	• / •
H / V size / H / V position	• / •
tilt	•
pincushion / pinbalance	• / •
trapezoid / parallelogram	• / •
color temperature / color calibration	• / •
H / V moire	• / •
vertical linearity / corner distortion	– / •
H / V convergence	– / –
automatic / manual degauss	• / •
zoom / frequency display	– / •
OSD timer / OSD position	– / •
OSD language(s)	5

max. refresh rates in Hz by resolution	
640 x 480	160
800 x 600	135
1024 x 768	105
1152 x 864	90
1280 x 1024	75
1600 x 1200	65
1600 x 1280	–
1920 x 1440	–
2048 x 1536	–

approvals / standards	
Plug & Play, DDC1/2B	•
Power-Management:	
Energy Star / Energy-Label	• / •
TCO 99	•
MPR II / TCO95	• / –
TÜV GS / TÜV Ergonomie	• / •
EN 29241 / DIN ISO 9241-3, -7, -8	• / •
Compatible with Mac	•

connections	
15 pin. Mini-D-Sub	•
BNC	–
headphone plug	–
audio in	–

accessories	
user manual (languages)	17
power cable	•
video connection 15 pin. Mini D-Sub	• (fixed)
audio cable	–

physical specification	
size (w x h x d) in mm	410 x 429 x 435
net / gross weight in kg	15,5 / 18,5

** Adjustable without using the OSD menu system. If the selection control is turned clockwise the adjustment menu for contrast appears, if it is turned anticlockwise the adjustment menu for brightness appears.*

January 2002, errors and omissions exempt.

Germany
MAXDATA Computer GmbH & Co. KG
Elbestraße 12-16 • D-45786 Marl

Austria
MAXDATA Computer GmbH
Ignaz-Köck-Straße 9 • A-1210 Wien

Switzerland
MAXDATA Computer AG
Haldenstrasse 5 • CH-6340 Baar

Netherland
MAXDATA Benelux B.V.
Hogehilweg 8 • NL-1101 CC Amsterdam Z-O

Belgium
MAXDATA Benelux B.V.
De Vunt 17 • B-3220 Holsbeek

France
MAXDATA S.A.R.L.
1, rue de Gevaudan • SILIC 1726
F-91017 EVRY Cedex

Great Britain
MAXDATA UK Limited
The MAXDATA Centre
Downhill Road • Brackwell, Bershire
RG12 1QS • GB

www.belinea.com